



SuperSpeed USB-C to HDMI/VGA 4-in-1 Docking Converter

USB 3.1 C Male to HDMI or VGA Converter, Two-Port USB 3.0 Hub and SD Card Reader, Aluminum, Black

Part No.: **152631**

Easily connect a USB Type-C device to an HDMI or VGA display, USB peripherals and SD memory card.

The Manhattan SuperSpeed USB-C to HDMI/VGA 4-in-1 Docking Converter establishes a fast, simple and convenient link between newer USB type-C equipped media sources (computers, tablets, Smartphones, etc.) and existing HDMI/VGA displays (monitors, projectors, etc.), in either mirror- or extended-display mode. Create a mini-workstation by adding any USB 3.0 peripheral such as a mouse, keyboard, hub, external memory device and more with the integrated USB 3.0 ports and SD card slot.

The Manhattan SuperSpeed USB-C to HDMI/VGA 4-in-1 Docking Converter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your type-C device. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and work spaces neat and orderly.

Features:

- Multi-function docking converter connects a USB Type-C port to an HDMI or VGA display, two-port USB 3.0 hub and SD Card Reader
- Offers Ultra-High-Definition (UHD) 4K@30Hz video and audio with an HDMI connection or HD 1080p video with a VGA connection
- Mirror or Extended display modes support video resolutions up to 1080p@60Hz or 3840x2160 at 30 Hz (4K) Full UHD
- Provides a USB 3.0 two-port hub to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- USB-A ports support SuperSpeed (5 Gbps) data transmission and charging up to 7.5 W (5 V / 1.5 A); BC1.2 compliant
- Easy access to media and content management with read/write/copy SD slot; supports automatic card detection and data transfer speeds up to 480 Mbps
- USB-C supports 5 Gbps data transmission
- Angled, aluminum housing makes this durable converter the perfect desktop or travel companion
- Compatible with all USB Type-C, DP Alt mode supported desktops, notebooks and

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

tablets including Apple MacBook, Chromebook Pixel and more

- Compliant with DisplayPort 1.2 Alternate Mode (DP Altmode)
- Plug and Play
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Three-Year Warranty

Specifications:

Standards and Certifications

- USB 3.1
- HDMI
- HDCP 1.4
- CE
- FCC
- RoHS2
- WEEE

General

- Video Resolutions: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200, 3840 x 2160p at 30 Hz, 4K
- USB A ports: 5 Gbps
- Supported flash cards: SD / SDHC / SDXC / EXTREME SD / EXTREME II SD / EXTREME III SD / ULTRA SD / ULTRA II SD / ULTRA II SD P PLUS / SD-ULTRA-X / ULTRA SPEED SD / SD PRO / SD ELITE PRO / HS SD / MMC / MMC 4.0 / HS MMC / HS RS MMC / RS MMC / RS MMC 4.0 / MMC Mobile
- Transfer speed: up to 480 Mbps
- 24-AWG cable gauge
- Bus powered
- Mylar and aluminum shielding
- Withstanding voltage: 300 VDC
- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm

Connections

- One USB Type-C 24-pin, male
- One HDMI 19-pin, female
- One VGA 15-pin female
- Two USB Type-A 4-pin, female
- One SD memory slot

Physical

- Length: 8 cm (3 in.)
- Weight: 73 g (2.2 oz.)
- Housing: Aluminum

Operating Environment

- Operation Temperature: 32 – 122°F (0 – 50°C)
- Storage Temperature: -22 – 176°F (-30 – 80°C)
- Humidity (noncondensing): 5 – 90%

System Requirements

- Windows 8.1/10 or Linux or Mac 10.10.5 or above

Package Contents

- SuperSpeed USB-C to HDMI/VGA 4-in-1 Docking Converter
- Quick Instruction Guide

