



## SuperSpeed+ USB-C 3.1 to DVI Converter

C Male to DVI Female, Black

Part No.: **152051**

Easily connect a USB type-C source with a DVI display

The Manhattan USB 3.1 to DVI Converter establishes a fast, simple and convenient link between newer USB type-C equipped media sources (computers, tablets, etc.) and existing DVI displays (monitors, projectors, etc.). The Manhattan USB 3.1 to DVI Converter is easy and quick to install--no complicated configuration or setup required. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and work spaces neat and orderly. Extend the service life of your equipment, and fully realize the investment and value of your DVI displays, projectors and peripherals with Manhattan USB 3.1 to DVI converters.

### Features:

- Converts a USB signal to a DVI video display
- Enjoy Ultra High-Definition (UHD) images on a DVI monitor, projector or other display device
- Supports video resolutions up to 3840x2160p@30Hz, 4K, Full UHD
- Compliant with DisplayPort 1.2 Alternate Mode (DP Altmode)
- Plug and Play; requires no external power supply
- Compatible with all USB type-C supported desktops, notebooks and tablets including Apple MacBook, Chromebook Pixel and more
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime Warranty

### Specifications:

#### Standards and Certifications

- USB 3.1
- DVI
- CE
- FCC
- RoHS2

*For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).*

*All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.*

- WEEE

#### Connections

- USB type-C, 24-pin, male
- DVI, 24-pin, female
- Shielded

#### Video Resolutions

- 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200, 3840 x 2160p@30Hz, 4K

#### Physical

- 32-AWG cable gauge
- Mylar and aluminum shielding
- Thermal plastic casing
- Length: 8 cm (3 in.)
- Weight: 31 g (1.1 oz.)
- Shielded
- Housing: ABS plastic

#### Operating Environment

- Operation Temperature: 32 ~ 122°F (0 ~ 50°C)
- Storage Temperature: -4 ~ 185°F (-20 ~ 85°C)
- Humidity (noncondensing): 0 ~ 96%

#### System Requirements

- Windows XP/Vista/7/8.1/10 or Linux or Mac 9.x/10.x or above

#### Package Contents

- SuperSpeed+ USB 3.1 to DVI Converter



